



TECHNICAL DATA SHEET

TDS 04.008

Product

CEBOSI DECORO

Description

CEBOSI DECORO is a water based, acrylic, washable, coating for interiors with special silver or gold reflections. It can be used as supplied or it can be coloured to create refined aesthetic effects in classic or modern rooms.

It is available in Argento, Oro Ducato, Oro Veneziano, Oro Zecchino bases.

CEBOSI DECORO is available in 1 litre and 5 litres containers.

Surface treatment of the substrate

It can be applied over all substrates such as gypsum, lime or cement based fine render as long as properly treated. In case of rough substrates repair the surface with levelling paste.

Carefully clean the surface and, if necessary, repair and level the substrate. Apply CEBOSI FONDO with a short pile roller, in one or two coats to reach a perfect cover of the substrate. In case of substrates which are highly absorbent, give a first coat of CEBOSI FONDO diluted 30% with water.

Colouring

CEBOSI DECORO can be coloured with CeboColorStation tinting system or with CEBOKIT universal colorants in the quantities indicated on our Colour Cards. It is also possible to create different shades in addition to those presented on our Colour Cards by varying the quantities or by mixing different colorants. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the same lot number.

Application

Apply CEBOSI DECORO in two coats on the surface previously prepared with CEBOSI FONDO. Apply the first coat with an inox or plastic trowel in a uniform layer of product to cover perfectly the substrate and to attain a smooth surface.

When the first coat is completely dry (after about 4-6 hours) apply the second coat always by trowel in crossed movements to attain the **trowelled effect**.

It is also possible to decorate with a **striped effect** applying the product in the desired direction (slanting, vertical, horizontal) in long stripes, going over the surface in the opposite alternating directions, to eliminate the excess of product.

Useful suggestions

CEBOSI DECORO can also be applied over metal, wood, glass or plastic. It is however important to treat the substrate with suitable primers.

VOC Classification (2004/42/CE Directive)

Product category: Decorative effect coating (I)

Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l.

CEBOSI DECORO contains: 25 g/l VOC

Technical characteristics

Estimated Coverage: 4 – 5 m²/litre, in two coats, according to the method of application and type of finish chosen.

Appearance: liquid

Specific weight: 1.2 g/cm³

pH: 8.5 – 9

Resistance to washing: The product withstands ordinary cleaning maintenance.

Drying time: 4-6 hours according to ambient temperature and relative humidity.

Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

Safety warnings

CEBOSI DECORO does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet implies the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.